

PRODUCT

K2004



we connect sound to the community

FEATURES

- High Quality CLASS-D Professional Amplifier
- 4CH Dnate™ Digital Audio Input
- Built-in DSP
- EasyControl of Equipment Through Front Panel With OLED and PC GUI
- Easy One-Touch Front Dust Filter Cleaning
- Simultaneous Control of Multiple Amplifiers Via PC GUI
- Up to 340 ms Delay Time Adjustable
- Frequency Band Adjustment Using HPF and LPF
- Unlimited Preset Creation For Environment-Optimization

SPECIFICATIONS

8Ω / 4Ω / 2Ω STEREO MODE (-20ms Burst)	300W / 500W / 800W	8Ω / 4Ω Bridged Mono Mode (-20ms Burst)	1000W / 16000W(800W)
Input Sensitivity	+4dBu	Gain (STEREO & MONO / BRIDGE)	32dB / 38dB
S/N	≤92dB	THD (1/3W Rated Power)	≥0.5v%
Frequency Response (1W, ±1dB / 8Ω)	20Hz~20kHz	DSP Specification (8.24 Format)	32bit Fixed Point
A/D, D/A	24bit Conversion (Sampling Rate : 48kHz)	DSP Function	Input Gain, Parametric EQ, GPF, LPF, Limiter, Delay



Head office 160-1, Jong-ro, Jongro-gu, Seoul Rep. of Korea Tel +82.10.5223.5997 www.koon-audio.net